




AC-DC 15W

6A-151DUXX




DESKTOP IN-LINE (US Power Cord)

Features:

- IEC/EN/UL/CUL 62368
- Universal AC Input 90~264Vac
- Regulated Output With Low Ripple Noise
- 100% burn in test
- 1 year warranty
- CEC,DoE Level VI
- WEEE / ROHS 2.0 / REACH 2.0
- Safety : UL/CUL, FCC



Dimension:



Model No.	O/P Voltage	O/P Current	O/P Watts
6A-151DU05A	5.0V	2.0A	10.0W
6A-151DU05	5.0V	2.5A	12.5W
6A-151DU06	5.95V	2.1A	12.49W
6A-151DU09	9.0V	1.7A	15.3W
6A-151DU12A	12.0V	1.0A	12.0W
6A-151DU12	12.0V	1.25A	15.0W
6A-151DU15	15V	1.0A	15.0W
6A-151DU24	24V	0.625A	15.0W

Specification:

Input	Voltage	AC 90V~264V Universal Full Range
	Frequency	47-63Hz
	Current	300mA
	Leakage Current	< 0.25mA
Others Protection	Start up time	< 4000mS @115VAC Full Load
	Rise time	<100mS
	Hold up time	>20mS @ 230Vac/50Hz input
	Protection	OCP/OVP/SCP
	Cooling	Natural Convection Cooling
Environment	Temperature	Operating: 0~40°C;Storage: -10~+70°C
	Humidity	Operating: 20%~85%;Storage: 10%~95%(Non Condensing)
M.T.B.F	50k Hours MIL-HDBK-217F @ 115VAC/ 230VAC Full Load Ambient : 25°C	
Safety Regulation	UL 62368-1, CSA C22.2 No.62368-1, IEC62368-1, EN62368-1	
EMC	EMI	FCC CFR 47 PART 15B, EN55032, EN61000-3
	EMS	EN55024(EN61204-3), EN61000-4
Energy Efficiency	Average active efficiency	10W> 78.7% Min @ 110Vac / 60Hz input ; 12.5W> 80.21% Min @ 110Vac / 60Hz input 12W> 82.96% Min @ 110Vac / 60Hz input ; 15W> 84.13% Min @ 110Vac / 60Hz input
	No-load power consumption	> 0.1W Min @ 110Vac / 60Hz input

英格爾科技股份有限公司
ENG ELECTRIC CO.,LTD.

台灣桃園市龜山區民生北路1段536號5樓
5F., No. 536, Sec. 1, Minsheng N. Rd.,
Gueishan Dist., Taoyuan City 333016,
Taiwan (R.O.C.)



TEL:886-3-212-1122 FAX:886-3-212-1570 E-mail:eng@eng.com.tw http://www.eng.com.tw

